

GH TEXFLEX X-TREME

SEMI-RIGID ATTACK HOSE ACCORDING TO DIN EN 1947

MATERIAL CONSTRUCTION

Jacket:

- High-tenacity polyester yarn, spun-dyed, circular woven
- Monofilament coil in weft keeps hose semi-rigid
- Specially designed for high pressure and very tight bending radii

Lining:

- High-grade EPDM rubber, flexible at low temperatures, also suitable for hot water

ADVANTAGES

- ✓ Exceptionally lightweight, anti-kinking and highly flexible (even at low temperatures)
- ✓ Very small bending radius and high abrasion resistance thanks to special G&H 4Z weaving system
- ✓ Easy to roll up on reels
- ✓ Less susceptible to tangling and stretching
- ✓ Very good adhesion between the rubber and jacket
- ✓ Distinctive design with contrasting weave for high visibility

PRESSES

Working pressure:

Specifications apply only to the hose (medium water, 20°C). For hose assemblies with couplings, the possible operating pressure may be lower than specified above due to the nominal pressure of the couplings or the type of assembly.

Maximum operating pressure:

Approval for this can only be given by the manufacturer after clarification of the exact area of application.

[To the binding instructions >>](#)

AT A GLANCE

Temperature ranges

-20 °C bis 80 °C

(Specifications apply to Water)

Standard colors

orange / yellow

Areas of application

- Fast attack firefighting

CONTACT

Gollmer & Hummel GmbH
Gässlesweg 23
75334 Straubenhardt

T +49 (0) 7082 9434-0

F +49 (0) 7082 9434-99

E info@gollmer-hummel.de

DATASHEET

Inside diameter in mm	Weight in g/m	Burst pressure in bar	Bending radius in mm	DIN number	Approval
25	246	150	160	DIN EN 1947	DIN EN 1947

i Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.

PRODUCT IMAGES

